



Valid for

StrataCore 3.x

OSes

RH Linux

FreeBSD

Exceptions

Connect to the cache GUI with your browser.

https://xxx.xxx.xxx.xxx:8443

Under Configuration Files
Select Open
Select the Default configuration

Under Configuration
Select Content
Select Access Control
Select Profiles and Policies
Check for a profile 'all scr all' if it does not exist then*
'NEW' profile
Type CONNECT in the window as the profile name.
Select 'Method' then submit.
Replace GET with CONNECT --uppercase is required

Submit
'NEW' profile
You must make three port profile jobs.
High_ports
1025-65535

Submit
SSL_port
443

Submit
SSL_port2
563

Submit

Cache Access Policy
Check for a Cache Access Policy 'allow all' if it does not exist**
'NEW' Cache access policy
Select 'deny'
Move 'CONNECT' to matched profiles
Move 'High_ports' 'SSL_port' 'SSL_port2' to unmatched profiles
Submit

The new cache access policy must be above the 'allow all' policy.
Select the policy and press the 'Move up' button, if necessary.

Under Configuration
Select Commit

***Make an 'all src all' profile**

'NEW' profile
Input 'all' , accept default profile type, then submit
Input 'all'
Submit

****Make an 'allow all' policy**

'NEW' policy
Move 'all' to matched profiles
Submit