



LINQ

55" PRO TOUCH SERIES

LINQ Pro Touch Series tablets combine powerful performance with a slim form factor to deliver interactive digital experiences. Designed for continuous commercial use, the tablets use AC-DC power, eliminating the need for battery power and making them ideal for fixed applications such as digital signage, self-service kiosks and interactive guided selling.

Equipped with a front facing camera and integrated sensors, the screens enable consumer detection, identify audience demographics and can deliver highly personalized customer experiences. A variety of I/O options provide the versatility to connect multiple accessories and peripherals to customize your solution. The robust content management platform provides integrated media scheduling and application, content and device management across diverse locations.




COMMERCIAL-GRADE RELIABILITY

Operate in rugged and demanding environments without interruption



ALL-IN-ONE INTELLIGENT SCREEN

Combines powerful performance with a slim design



INTEGRATED HARDWARE AND SOFTWARE

Manage content updates and devices across diverse locations

ADDITIONAL FEATURES

- Variety of sizes: 11.6", 15.6", 18.5", 21.5", 32", 43" and 55"
- Flexible Mounting Options: Portrait or Landscape with VESA standard mount fixations
- Accessory Integration: Scanners, card readers and more

Description	Specification	
	Standard	Plus
Model Description	LINQ 55" Pro Touch Series	
Power	Input: 100-240V-50/60Hz AC Output: 24V DC Screw Lock	
Operating System	Android 8.1 / Linux 4.4 Kernel	
Memory	2 GB Dual-channel DDR3-1600 (800 MHz)	4 GB Dual-channel DDR3-1600 (800 MHz)
CPU	Six-core Rockchip RK3399 ARM 64-bit processor, up to 2.0 GHz Dual-core ARM Cortex-A72 and Quad-core ARM Cortex-A53	
GPU	ARM Mali-T860 MP4 Quad-core GPU	
Storage	32 GB high-speed eMMC 5.1	64 GB high-speed eMMC 5.1
Display Panel	55" IPS, 1920 x 1080, 450 Nits Brightness, 89° Viewing Angle	
Touch Panel	10-point capacitive touch panel	
HDMI	One HDMI 2.0 input, one HDMI 2.0 output	
Auxiliary Audio	One 3.5 mm, One Toslink S/PDIF	
Speakers	Four 5W Speakers	
Network	Gigabit Ethernet RJ45, 2.4/5 GHz Dual-band Wi-Fi (IEEE 802.11a/b/g/n/ac), Bluetooth 4.0, 4G LTE (optional)	
Antenna	One WiFi/Bluetooth, One 4G LTE	
USB	Five USB 2.0 (One service)	
Front Camera	8 Megapixel	
Other I/O	Buttons: Home/Recovery, Vol +/-, Brightness +/-, Reset, Custom (*) SD Card, 4G module and SIM card bay	
Mount	VESA 400 x 200 mm	
Dimensions	1278 x 754 x 62.5 mm / 50.32 x 29.69 x 2.46 in	
Net Weight	38.6 kgs / 85.10 lbs	
Enclosure	Metal casing with aluminum frame	
Storage Temperature	-15° - 65° C / 5° - 149° F	
Working Temperature	0° - 50° C / 32° - 122° F	
Storage/Working Humidity	10 - 90% Non-condensing	
Warranty¹	1 year included, extended warranty available	
Optional Upgrades²	4G LTE: Quectel EG25-G LTE Module with internal SIM card slot	

¹Extended warranties must be added at time of purchase
²4G Module and SIM card not included

Option 1
On-premise CMS



Option 2
Cloud-based CMS



LINQ

Powered by
STRATACACHE

Optional Accessories

- Barcode Scanner**
- Credit Card Reader**
- Printer**
- Camera (External)**
- Mobile Sensor**
- Auxiliary Audio**
- Fingerprint Scanner**